

LEGEND

LDP Boundary

Subject Lots

Subject Lots - Rear Loaded Terrace

Subject Lots - Narrow Frontage

No Vehicle Access

Dwelling Orientation (Provision 6)

• • • Uniform Fencing by Developer (Provision 6a)

Boundary Wall Permitted (Provision 8, 9a)

Designated Driveway Crossover (Provision 10b) (indicative design)

Single Garage Location (for narrow frontage lots)

Double Garage Location

Trees proposed for retention

Reciprocal Right of Access Easement

Foot Path

NOTES:

Determination of which trees can be retained and which require removal is contingent on review by a qualified arborist to be undertaken as part of civil construction.



LOCAL DEVELOPMENT PLAN PROVISIONS **STAGE 4 DAWSON VILLAGE**

- 1. This Local Development Plan (LDP) applies to those lots indicated on the LDP plan.
- 2. The requirements of the City of Busselton Local Planning Scheme No. 21 and Residential Design Codes are varied as shown on the LDP. The requirements of the Residential Design Codes (R-Codes) and Scheme shall be
- 3. Consultation with adjoining or other landowners to achieve a variation provided for by the LDP is not required.
- 4. Minor variations to the requirements of this LDP may be approved by the City of Busselton.

Street Setbacks, Dwelling Orientation and Fencing

- 5. Street setbacks shall be as follows:
- a) 4.0m minimum street setback for Narrow Frontage lots, no averaging permitted.
- b) With the exception of Narrow Frontage lots, 6.0m minimum setback for lots oriented to Yebble Drive (averaging permitted).
- c) 2.0m minimum street setback for lots with access from a laneway.
- 6. Where dwelling orientation is specified on the plan, the dwelling is to address this frontage with clearly defined entry points visible and accessed from the frontage. Street setback and front fence requirements pursuant to the R-Codes are to be applied to this frontage, with the following exceptions:
- a) For Lot 92 Yebble Drive, a solid masonry wall to a height of 1.8m is permitted to the 11.15m truncation to the Harlequin Boulevard / Yebble Drive intersection.
- b) For Lots 472, 475 and 476 Yebble Drive, front fencing is to comprise a solid section to a maximum height of 0.75m (excluding Colorbond) with a maximum overall height of 1.2m above ground level.
- 7. Lot 480 Stylaster Circuit:
- a) A side setback of 4.0m (no averaging) to Yebble Drive is required; and
- b) Any side fencing to Yebble Drive is to be visually permeable above 1.2m of natural ground level.

Lot Boundary Setbacks and Building Height

- 8. For Lots 469 and 62 Harlequin Boulevard, Lots 51 and 52 Yebble Drive and Lots 133 and 481 Flounder Street, walls may be built up to a lot boundary behind the street setback, within the following limits:
- a) No maximum length where constructed between Lots 469 and 62 Harlequin Boulevard, Lots 51 and 52 Yebble Drive and Lots 133 and 481 Flounder Street; and
- b) To the other side boundary, walls not higher than 3.5m up to two-thirds the length of the lot boundary behind the street setback.
- 9 For Lots 69 82 Orca Lane
- a) Boundary walls permitted to both side boundaries with no maximum length where located behind the street setback (excludes secondary street frontage).
- b) Building heights (including boundary walls) shall comply with Table 3 (Category B) of the R- Codes, excepting that the top of an external wall (roof above) is permitted to a maximum of 7.0m.
- c) Boundary Setbacks (including secondary street): 1.0m minimum permissible for wall height 7.0m or less with or without major openings.

Garages and Access

- 10. For Lots 469 and 62 Harlequin Boulevard, Lots 51 and 52 Yebble Drive and Lots 133 and 481 Flounder Street the following requirements apply
- a) Garages are to be setback a minimum of 0.5m behind the dwelling alignment.
- b) Driveway crossovers shall be shared jointly and consolidated within the Designated Driveway Crossover location depicted on the plan. Consolidated driveway width shall be a maximum 4.0m where intersecting with the road reserve.
- c) Driveways may be closer than 0.5m from a side lot boundary.
- 11. The following requirements apply to rear loaded terrace lots:
- a) Vehicle and garage access must be from the rear laneway
- b) Garages are to be setback a minimum of 1.5m from the rear laneway.
- c) Driveways may be closer than 0.5m from a side lot boundary.

ROAD/PATH INFORMATION SOURCE: STANTEC YYMMDD: 200615 PYMMDD: 200615

DWG REF: 200615_Dawson Stage 4B_c Reference Roads

HATCH

RobertsDay PROJECTION: PCG94 CADASTRAL INFORMATION SIZE A3 1:2000 SOURCE: THOMPSONS YYMMDD: 200616

DWG REF: BASEFILE-Stages4A+B-1.2&5A dwa

Dawson Estate

City of Busselton G PROV + LEGEND UPDATES 210809 PROV UPDATES 2,5,6 &7 210721 DP DP PROVISION 9 200903 DRAW NO. REV. JOB CODE 200820 II DP YYMMDD DRAWN APPR'D D COB MODS REV DESCRIPTION PGPDAW RD1 306 G

VASSE STAGE 4 - LOCAL DEVELOPMENT PLAN - AMENDMENT NO.2